

# Swing Sump Pump Check Valve

**PVC**

**TYPE 1**

## FEATURES

- Constructed from durable Type 1 PVC
- Weighted Buna-N flapper seal for low pressure seal
- Full flow design reduces flow loss
- Compression end connections for easy installation
- Includes 1-1/4" & 1-1/2" Buna-N compression gaskets for use with both 1-1/4" & 1-1/2" pipe.
- Can be installed vertically or horizontally
- Pressure rating: 125 PSI at 75° F (24° C)
- Meets ASTM D2466 Standard
- Not for use with compressed air, gases or potable water

MLP79545



**1 YEAR**  
LIMITED WARRANTY

# Swing Sump Pump Check Valve

**PVC**

TYPE 1



## Application

One way check valve prevents backflow of water into sump pit.

## Dimensional Data

Model	MLP79545
IPS Pipe Size	1-1/2 in.
Weight	.7 lbs.
A	2.88 in.
B	2.18 in.
C	5.73 in.
D	2.95 in.

## Product Specifications

NO.	PART	MATERIAL	QTY
1	Compression Nut	PVC	2
2	Compression Gasket*	BUNA-N	4
3	Upper Body	PVC	1
4	Flapper Disc	PVC	1
5	Flapper Seat	BUNA-N	1
6	Lower Body	PVC	1

\*Both 1-1/2" & 1-1/4" compression gaskets are included. 2 of each size.

